



ESTABLISHED IN 1978

PANEL AIR CONDITIONER

COOLING
YOUR INDUSTRY
OPTIMISING
YOUR PROCESS



40⁺

YEARS OF
EXCELLENCE IN
REFRIGERATION

PANEL AIR > CONDITIONER



ESTABLISHED IN 1978

State of Art Enclosure Cooling Range With Highest Energy Efficiency While Handling Peak Heat Load

FEATURES



Energy Efficient
Balanced Design



High Ambient
Temperature Efficient



Combination of
High Efficiency
Heat Exchanger & Air Flow



GI Sheet Metal With
Powder Coated



Maximum Utilization of Natural
Law of Heat Transfer



Easy Mount Studs
For Simple Installation



CE Certified
European Conformity

HIMALAYA'S panel air conditioner units are excellent match to your electrical and electronic panel cooling needs.

These units are designed specifically understanding the high sensible cooling requirement panel able to run non stop for long hours. High reliable components and electronics supported by high ambient design ensure your machines work smoothly all year round.

The model is available with various capacity ranged from 500 W to 8500 W on single chassis. Them mounting, power supply & refrigerant options are available.

Application :



CNC/VMC/HMC
Machine Panel



Telecommunication
Panel



Electrical/Control
Panel



Drive/Robot
Panel



Automation
Panel



Server
Panel



MODEL	COOLING CAPACITY IN WATTS (kcal/h)	POWER		REFRIGERANT GAS	MOUNTING TYPE	DIMENSION MM			WEIGHT KG APPROX
		WATTS	INPUT			WIDTH	DEPTH	HEIGHT	
PACS-250-DS	250 (215)	230	220-240V AC, 1 Ph, 50 Hz	R134a	DOOR/SIDE	340	240	475	23
PACS-550-DS	550 (473)	320	230 V AC, 1 Ph, 50/60 Hz	R134a	DOOR/SIDE	340	240	475	23
PACS-1050-DS	1050 (903)	600	230 V AC, 1 Ph, 50/60 Hz	R134a	DOOR/SIDE	340	245	640	30
PACS-1550-DS	1550 (1333)	850	230 V AC, 1 Ph, 50/60 Hz	R134a	DOOR/SIDE	440	350	1000	59
PACS-2550-DS	2550 (2193)	1350	230 V AC, 1 Ph, 50/60 Hz	R134a	DOOR/SIDE	440	350	1000	63
PACS-4550-S	4550 (3912)	1700	230 V AC, 1 Ph, 50/60 Hz	R134a / R22	SIDE	530	620	1400	104
PACS-6550-S	6550 (5632)	2200	440 V AC, 3 Ph, 50/60 Hz	R134a / R22	SIDE	530	720	1400	114
PACS-8550-S	8550 (7352)	2600	440 V AC, 3PH, 50/60 Hz	R134a / R22	SIDE	530	720	1400	134

*Available on demand in stainless steel 304 body, top mount & power supply options.

*Due to continuous product improvements & its incorporation, HIMALAYA reserves the right to changes the design, technical specifications & dimensions without prior notice.

Global Presence



Range : 500w-8500w

Thermal Management Protects
Components & Extend Their Service Life

Guaranteed Constant Temperature
Inside The Enclosures.



HIMALAYA REFRIGERATION INDUSTRIES

Plot No 2222, Kranti Gate, Metoda G.I.D.C.,
Kalawad Road, Rajkot. 360021 (Guj) INDIA.

02827 - 287031/297031
9974 5555 11 | 9979 5555 11

info@himalayaref.com
www.himalayaref.com

